

IKON XD SERIES



STRENGTH WITH A SOFTER SIDE.

With a solid tubular frame and a wide range of cutting sizes, the IKON XD brings power and flexibility to all yard sizes. A plush high back seat and large tires provide comfort and stability, hour after hour.

3 YEAR
OR
300 HOURS
WARRANTY

| DESIGNATION | IKON XD 42 | IKON XD 42 | IKON XD 52 | IKON XD 52 | IKON XD 60 |
|--|---|----------------------------|----------------------------|----------------------------|------------------------------|
| MODEL # | 915265 | 915268 | 915266 | 915267 | 915273 |
| ENGINE | Kohler® 7000 Series™ | Kawasaki® FR600 | Kohler® 7000 Series™ | Kawasaki® FR691 | Kawasaki® FR691 |
| HORSEPOWER | 22 hp | 18 hp | 24 hp | 23 hp | 23 hp |
| DISPLACEMENT (CC) | 725 cc | 603 cc | 725 cc | 726 cc | 726 cc |
| DRIVE SYSTEM | Hydro-Gear® EZT Transaxles | Hydro-Gear® EZT Transaxles | Hydro-Gear® EZT Transaxles | Hydro-Gear® EZT Transaxles | Hydro-Gear® EZT Transaxles |
| FUEL CAPACITY | 2.8 Gallon (10.5L) | 2.8 Gallon (10.5L) | 2.8 Gallon (10.5L) | 2.8 Gallon (10.5L) | 2.8 Gallon (10.5L) |
| GROUND SPEED (APPROXIMATE MPH) (FWD/REV) | 7 mph / 3 mph | 7 mph / 3 mph | 7 mph / 3 mph | 7 mph / 3 mph | 7 mph / 3 mph |
| STARTER | Electric | Electric | Electric | Electric | Electric |
| CARB COMPLIANT | No | No | No | No | No |
| DECK MATERIAL | 11 ga | 11 ga | 11 ga | 11 ga | 11 ga |
| DECK CONSTRUCTION | Fabricated | Fabricated | Fabricated | Fabricated | Fabricated |
| NUMBER OF SPINDLES | 3 | 3 | 3 | 3 | 3 |
| BLADE TIP SPEED (FPM) | 17,000 | 17,000 | 17,000 | 17,000 | 17,000 |
| SPINDLE MATERIAL | Steel | Steel | Steel | Steel | Steel |
| SPINDLE SHAFT | Steel | Steel | Steel | Steel | Steel |
| SPINDLE BEARINGS | Sealed | Sealed | Sealed | Sealed | Sealed |
| DECK DRIVE | Belt | Belt | Belt | Belt | Belt |
| DECK ENGAGEMENT | Electric Warner | Electric Warner | Electric Warner | Electric Warner | Electric Warner |
| DECK LIFT SYSTEM | Foot Operated | Foot Operated | Foot Operated | Foot Operated | Foot Operated |
| CUTTING WIDTH | 42 in | 42 in | 52 in | 52 in | 60 in |
| CUTTING HEIGHTS | 1.5 in-4.5 in | 1.5 in-4.5 in | 1.5 in-4.5 in | 1.5 in-4.5 in | 1.5 in-4.5 in |
| CUTTING POSITIONS | 13 | 13 | 13 | 13 | 13 |
| WHEELS FRONT AXLE | Fixed | Fixed | Fixed | Fixed | Fixed |
| WHEELS (FRONT) | 11 in x 4 in - 5 in | 11 in x 4 in - 5 in | 11 in x 4 in - 5 in | 11 in x 4 in - 5 in | 11 in x 6 in - 5 in |
| WHEELS (BACK) | 20 in x 8 in - 8 in | 20 in x 8 in - 8 in | 20 in x 10 in - 8 in | 20 in x 10 in - 8 in | 20 in x 10 in - 8 in |
| SEAT | High Back w/ Armrests | High Back w/ Armrests | High Back w/ Armrests | High Back w/ Armrests | High Back w/ Padded Armrests |
| HOURLY METER | Standard | Standard | Standard | Standard | Standard |
| WEIGHT | 592 lbs | 594 lbs | 637 lbs | 639 lbs | 671 lbs |
| LENGTH | 77.5 in | 77.5 in | 77.5 in | 77.5 in | 77.5 in |
| WIDTH | 54.2 in | 54.2 in | 63.4 in | 63.4 in | 72.2 in |
| HEIGHT | 40 in | 40 in | 40 in | 40 in | 40 in |
| WARRANTY (MACHINE) | 3 Year / 300 Hour | 3 Year / 300 Hour | 3 Year / 300 Hour | 3 Year / 300 Hour | 3 Year / 300 Hour |
| ATTACHMENTS & ACCESSORIES | 2 Bucket Bagger Kit, Mulching Kit, Trailer Hitch Kit, Headlight Kit, Spreader, Roller, Aerator, Dethatcher, Sprayer | | | | |

COMMERCIAL-STYLE DECK

4" deep fully fabricated with advanced airflow for an exceptional cutting performance.

TUBULAR STEEL FRAME

The Fully-welded steel frame provides strength and durability.

DIAL-OPERATED CUTTING HEIGHT

13 cutting positions at your fingertips allows for easy adjustments from 1 ½" to 4 ½" cutting height with the turn of a dial.

HYDROSTATIC EZT TRANSAXLE

Transaxles provide increased torque and a smooth operation for better control.

PLUSH SEAT

Options like the plush, adjustable highback seat with padded armrests allows for longer use and greater comfort.